

DS-2CE5582P(N)-VF



Key Features

- 1/3" DIS
- Electronic Day/Night
- 600 TVL horizontal resolution
- 2.8 ~ 12mm vari-focal lens
- Wide operating temperature range
- 3-axis adjustment

Specification

Model	DS-2CE5582P(N)-VF
Parameter	600 TVL DIS Indoor Dome Camera(Vari-focal)
Camera	
Image Sensor	1/3" DIS
Signal System	PAL/NTSC
Effective Pixels	720 (H) × 480 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON) 0.14 Lux @ (F1.4, AGC ON)
Shutter Time	PAL: 1/25 s to 1/100,000 s NTSC: 1/30 s to 1/100,000 s
Lens	2.8 - 12 mm @ F1.4 Angle of view: 80° - 27.2°
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 180°, Rotation: 0 - 355°
Day & Night	Electronic
Horizontal Resolution	600 TVL
Synchronization	Internal synchronization

Video Output	1Vp-p composite output (75 Ω/BNC) Test monitor out [1Vp-p composite output (75 Ω/BNC), device line]
S/N Ratio	More than 52 dB
BLC	On
General	
Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1 W
Dimension	Φ 136 × 101 mm (Φ 5.35" × 3.98")
Weight	500 g

Order Models

DS-2CE5582P-VF

DS-2CE5582N-VF

Dimensions

